

GASOLINE GENERATOR - 3000rpm
Technical Data- Open type

HYUNDAI

POWER PRODUCTS

Generator		HY30CLE
Rated Power	kVA	2.3
Max. Power	kVA	2.5
Phase/Wire		1 phase / 2 wires
Voltage	V	220
Voltage fluctuation		±1%
Frequency	Hz	50
Frequency fluctuation		±5%
Current	A	12.7
Display		Regular
Fuel tank capacity	L	15
Fuel Consumption	L/h	1.75
Sound level @7m	dBA	72
Battery Charge	V	12
Engine		IC210
Engine type		4 stroke, air-cooled gasoline, OHV type
Power	hp	6.5
Compression ratio		7.8:1
Bore*Stroke		68*54
Number of cylinder		1
Start		Manual/Electric
Displacement	cc	212
Oil capacity	L	0.6
Alternator		AL2.3
Power	kW	2.3
Power Factor		1
Voltage Regulator		AVR
Dimension and weight		
Net weight	kg	50
Gross weight	kg	52
Machine size (L*W*H)	mm	590x448x483
Loading Capacity FCL20'/40'HQ	mm	152/390



Optional Accessories	Electrical and Mechanical standards	Recommended spare part
 ATS control box (50A)	1 phase (2x16A European sockets) Displays: voltage Earth connection ATS connector Key electric start Intergrate steel tank coated with electrostatic paint Solid built and strong frame with anti-vibration and electrostatic coated Mechanical transmission: direct drive with a coaxial coupling	 Air filter core
 Remote controller		 Fuel filter element
 Push wheel kit	Other standards Available woking conditions: • Climate : tropical hot • Environmental temperature: 0-40°C • Humidity: 0-85%	